



Index	
B	= Width
D	= Outside Diameter
d	= Inside Diameter

## DOUBLE SPLIT SHAFT COLLARS IN MILLIMETERS

Product ID	Bore d	Diameter D	Width B	Allen Bolt / Clamp Bolt
PHLDSCM01	3.00	16.00	9.00	M3X8
PHLDSCM02	4.00	16.00	9.00	M3X8
PHLDSCM03	5.00	16.00	9.00	M3X8
PHLDSCM04	6.00	16.00	9.00	M3X8
PHLDSCM05	7.00	18.00	9.00	M3X8
PHLDSCM06	8.00	18.00	9.00	M3X8
PHLDSCM07	9.00	24.00	9.00	M3X10
PHLDSCM08	10.00	24.00	9.00	M3X10
PHLDSCM09	11.00	28.00	11.00	M4X12
PHLDSCM10	12.00	28.00	11.00	M4X12
PHLDSCM11	13.00	30.00	11.00	M4X14
PHLDSCM12	14.00	30.00	11.00	M4X14
PHLDSCM13	15.00	34.00	13.00	M5X16
PHLDSCM14	16.00	34.00	13.00	M5X16
PHLDSCM15	17.00	36.00	13.00	M5X16
PHLDSCM16	18.00	36.00	13.00	M5X16
PHLDSCM17	19.00	40.00	15.00	M5X16
PHLDSCM18	20.00	40.00	15.00	M6X16
PHLDSCM19	24.00	45.00	15.00	M6X16
PHLDSCM20	25.00	45.00	15.00	M6X16
PHLDSCM21	28.00	48.00	15.00	M6X16
PHLDSCM22	30.00	54.00	15.00	M6X16
PHLDSCM23	32.00	54.00	15.00	M6X16
PHLDSCM24	35.00	57.00	15.00	M6X16
PHLDSCM25	38.00	60.00	15.00	M6X16
PHLDSCM26	40.00	60.00	15.00	M6X16
PHLDSCM27	45.00	73.00	19.00	M8X25
PHLDSCM28	50.00	78.00	19.00	M8X25
PHLDSCM29	60.00	88.00	19.00	M8X25
PHLDSCM30	70.00	98.00	19.00	M8X25
PHLDSCM31	80.00	108.00	19.00	M8X25

### Tolerance

Bore d (3mm – 6mm)	+0.05mm / + 0.00mm
Bore d (7mm – 28mm)	+0.07mm / + 0.00mm
Bore d (30mm – 80mm)	+0.12mm / + 0.00mm
Diameter D	+0.12mm / - 0.12mm
Width B	+0.08mm / - 0.12mm

### Available In

AISI 1025 & Stainless Steel 304  
 Zinc Plated, Black Oxided & Self Colored  
 Other Tolerances and Sizes are available upon request



URS is a member of Registrar of Standards (Holdings) Ltd.

