



Index
B = Width
D = Outside Diameter
d = Inside Diameter

SOLID SHAFT COLLARS IN MILLIMETERS

Product ID	Bore d	Diameter D	Width B	Set Screw
PHLSCM01	4	8	5	M2.5
PHLSCM02	5	10	6	M3
PHLSCM03	6	12	8	M4
PHLSCM04	7	12	8	M4
PHLSCM05	8	16	8	M4
PHLSCM06	9	18	10	M5
PHLSCM07	10	20	10	M5
PHLSCM08	11	20	10	M5
PHLSCM09	12	22	12	M6
PHLSCM10	13	22	12	M6
PHLSCM11	14	25	12	M6
PHLSCM12	15	25	12	M6
PHLSCM13	16	28	12	M6
PHLSCM14	17	28	12	M6
PHLSCM15	18	32	14	M6
PHLSCM16	20	32	14	M6
PHLSCM17	22	36	14	M6
PHLSCM18	24	40	16	M8
PHLSCM19	25	40	16	M8
PHLSCM20	29	45	16	M8
PHLSCM21	30	45	16	M8
PHLSCM22	32	50	16	M8
PHLSCM23	35	56	16	M8
PHLSCM24	38	56	16	M8
PHLSCM25	40	63	18	M10
PHLSCM26	45	70	18	M10
PHLSCM27	50	80	18	M10
PHLSCM28	55	80	20	M10
PHLSCM29	60	90	20	M10
PHLSCM30	65	100	22	M10
PHLSCM31	70	100	20	M10
PHLSCM32	75	110	25	M12
PHLSCM33	80	110	25	M12

Tolerance

Bore d (4mm – 13mm)	+0.01mm / + 0.06mm
Bore d (14mm – 80mm)	+0.01mm / + 0.08mm
Diameter D	+0.127mm / + 0.000mm
Width B	+0.12mm / - 0.12mm

Available In

AISI 1025 & Stainless Steel 304
 Zinc Plated, Black Oxided & Self Colored
 Other Tolerances and Sizes are available upon request



URS is a member of Registrar of Standards (Holdings) Ltd.

