



### SOLID SHAFT COLLARS IN INCHES (IMPRIAL)

Product ID	Bore d	Diameter D	Width B	Set Screw
PHLSCM34	0.187	0.500	0.250	8-32UNC
PHLSCM35	0.250	0.500	0.281	8-32UNC
PHLSCM36	0.312	0.625	0.312	10-32UNC
PHLSCM37	0.375	0.750	0.375	10-32UNC
PHLSCM38	0.437	1.000	0.437	1/4BSW or 1/4-20 UNC
PHLSCM39	0.500	1.000	0.437	1/4BSW or 1/4-20 UNC
PHLSCM40	0.625	1.250	0.562	1/4BSW or 1/4-20 UNC
PHLSCM41	0.750	1.375	0.687	5/16BSW or 5/16-18 UNC
PHLSCM42	0.875	1.500	0.687	5/16BSW or 5/16-18 UNC
PHLSCM43	1.000	1.625	0.750	5/16BSW or 5/16-18 UNC
PHLSCM44	1.125	1.750	0.750	3/8BSW or 3/8-16 UNC
PHLSCM45	1.250	2.000	0.875	3/8BSW or 3/8-16 UNC
PHLSCM46	1.375	2.250	0.875	3/8BSW or 3/8-16 UNC
PHLSCM47	1.500	2.250	1.000	3/8BSW or 3/8-16 UNC
PHLSCM48	1.625	2.500	1.000	7/16BSW or 1/2-13 UNC
PHLSCM49	1.750	2.625	1.000	7/16BSW or 1/2-13 UNC
PHLSCM50	1.875	3.000	1.000	7/16BSW or 1/2-13 UNC
PHLSCM51	2.000	3.000	1.062	1/2BSW or 1/2-13 UNC
PHLSCM52	2.250	3.250	1.125	1/2BSW or 1/2-13 UNC
PHLSCM53	2.500	3.500	1.187	1/2BSW or 1/2-13 UNC
PHLSCM54	2.750	3.750	1.375	5/8BSW or 5/8-11 UNC
PHLSCM55	3.000	4.250	1.375	5/8BSW or 5/8-11 UNC

#### Tolerance

Bore d (0.187" – 0.875")	+0.001" / + 0.003"
Bore d (1.000" – 3.000")	+0.001" / + 0.004"
Diameter D	+0.005" / + 0.000"
Width B	+0.005" / - 0.005"

#### Available In

AISI 1025 & Stainless Steel 304  
 Zinc Plated, Black Oxided & Self Colored  
 Other Tolerances and Sizes are available upon request



URS is a member of Registrar of Standards (Holdings) Ltd.

