



SINGLE SPLIT SHAFT COLLARS IN MILLIMETERS

Product ID	Bore d	Diameter D	Width B	Allen Bolt/Clamp Bolt
PHLSSCM01	3.00	16.00	9.00	M3X8
PHLSSCM02	4.00	16.00	9.00	M3X8
PHLSSCM03	5.00	16.00	9.00	M3X8
PHLSSCM04	6.00	16.00	9.00	M3X8
PHLSSCM05	7.00	18.00	9.00	M3X8
PHLSSCM06	8.00	18.00	9.00	M3X8
PHLSSCM07	9.00	24.00	9.00	M3X10
PHLSSCM08	10.00	24.00	9.00	M3X10
PHLSSCM09	11.00	28.00	11.00	M4X12
PHLSSCM10	12.00	28.00	11.00	M4X12
PHLSSCM11	13.00	30.00	11.00	M4X14
PHLSSCM12	14.00	30.00	11.00	M4X14
PHLSSCM13	15.00	34.00	13.00	M5X16
PHLSSCM14	16.00	34.00	13.00	M5X16
PHLSSCM15	17.00	36.00	13.00	M5X16
PHLSSCM16	18.00	36.00	13.00	M5X16
PHLSSCM17	19.00	40.00	15.00	M5X16
PHLSSCM18	20.00	40.00	15.00	M6X16
PHLSSCM19	24.00	45.00	15.00	M6X16
PHLSSCM20	25.00	45.00	15.00	M6X16
PHLSSCM21	28.00	48.00	15.00	M6X16
PHLSSCM22	30.00	54.00	15.00	M6X16
PHLSSCM23	32.00	54.00	15.00	M6X16
PHLSSCM24	35.00	57.00	15.00	M6X16
PHLSSCM25	38.00	60.00	15.00	M6X16
PHLSSCM26	40.00	60.00	15.00	M6X16
PHLSSCM27	45.00	73.00	19.00	M8X25
PHLSSCM28	50.00	78.00	19.00	M8X25
PHLSSCM29	60.00	88.00	19.00	M8X25
PHLSSCM30	70.00	98.00	19.00	M8X25
PHLSSCM31	80.00	108.00	19.00	M8X25

Tolerance

Bore d (3mm – 6mm)	+0.05mm / + 0.00mm
Bore d (7mm – 28mm)	+0.07mm / + 0.00mm
Bore d (30mm – 80mm)	+0.12mm / + 0.00mm
Diameter D	+0.12mm / - 0.12mm
Width B	+0.08mm / - 0.12mm

Available In

AISI 1025 & Stainless Steel 304
 Zinc Plated, Black Oxided & Self Colored
 Other Tolerances and Sizes are available upon request



URS is a member of Registrar of Standards (Holdings) Ltd.

